

**DECLARATION OF PERFORMANCE**

n.87 CPR 01/07/2013

Pag. 1/3

1. Unique identification code of the product – type: **STIFERITE CLASS SK**
2. Batch number: **See CE mark label and marking on boards**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Thermal insulation for building**
4. Name, registered trade or registered trade mark name and contact address of manufacture:

**STIFERITE SpA**  
**Viale Navigazione Interna, 54**  
**35129 Padova (Italy)**

5. Name and contact address of authorised representative whose mandate covers: –
6. System or systems of assessment and verification of constancy of performance of the construction product: **AVCP 3**
7. In case of declaration of performance concerning a construction product covered by a harmonised standard:

**CSI S.p.A.**

**IDENTIFICATION NUMBER: 0497**

**Performed the test reports on the declared characteristics under system AVCP 3**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Istituto per le Tecnologie delle Costruzioni – Consiglio Nazionale delle Ricerche.**

**IDENTIFICATION NUMBER: 0970**

**Issued the European Technical Assessment ETA No. 09/0060, 10/0027, 12/0377, 13/0320 and 13/0871 according to the guide ETAG004 and to AVCP 1 and issued the certificate of conformity of the factory production and test reports**

9. Declaration performance:

| Essential Characteristics   | Performance                             |  | Harmonised technical specification |
|---|---|--|------------------------------------|
| Thermal resistance  | Thermal resistance $R_D/(m^2K/W)$       | <b>See table 1</b>                         | <b>EN 13165: 2016</b>              |
| Thermal conductivity  | Thermal conductivity $\lambda_D/(W/mK)$ |  |                                    |
| Thickness   | Thickness $d_N/(mm)$                    |  |                                    |
| Length and width  | < 1000 mm                               | <b>± 5 mm</b>                              |                                    |
|   | 1001 a 2000 mm                          | <b>± 7.5 mm</b>                            |                                    |
| Reaction to fire  | Reaction to fire $I$ (Euroclass)        | <b>E</b>                                   |                                    |
| Continuous glowing combustion   |   | <b>No harmonized test method available</b> |                                    |
| Durability of reaction to fire against heat, weathering, ageing/degradation |   | <b>Reaction to fire doesn't change</b>     |                                    |

|                            |                    |                       |                           |                       |                             |
|----------------------------|--------------------|-----------------------|---------------------------|-----------------------|-----------------------------|
| Declaration of performance | Stiferite CLASS SK | Rev. 3 del 10/04/2018 | Compiled by: F. Raggiotto | Verified by: L. Tolin | Approved by: P. Stimamiglio |
|----------------------------|--------------------|-----------------------|---------------------------|-----------------------|-----------------------------|

**DECLARATION OF PERFORMANCE**

| Essential Characteristics   | Performance   |   | Harmonised technical specification |
|---|---|---|------------------------------------|
| Durability of thermal resistance against heat, weathering, ageing/degradation | Durability of thermal resistance ageing/degradation                       | <b>Thermal resistance doesn't change</b>  | <b>EN 13165: 2016</b>              |
|   | Dimensional stability under specified temperature and humidity conditions | <b>See table 1</b>  |                                    |
|   | Deformation under specified compressive load and temperature conditions   | <b>NPD</b>  |                                    |
| Tensile strength  | Tensile strength perpendicular to the face /(kPa)                         | <b>80 [TR80]</b>  |                                    |
| Compressive strength  | Compressive strength/(kPa)  | <b>150 [CS(10/Y)150]</b>  |                                    |
| Durability of compressive strength against ageing/degradation                 | Compressive creep   | <b>NPD</b>  |                                    |
| Water permeability  | Water absorption - short term by partial immersion/(kg/m <sup>2</sup> )   | <b>0.2 [WS(P)0.2]</b>   |                                    |
|   | Water absorption - long term by total immersion /(%)                      | <b>2 [WL(T)2], for d<sub>N</sub> &lt; 120 mm<br/>1 [WL(T)1], for d<sub>N</sub> ≥ 120 mm</b> |                                    |
|   | Flatness after one sided wetting  | <b>≤ 10 mm [FW 10]</b>  |                                    |
| Water vapor transmission  | Water vapour transmission   | <b>MU 56 ± 2</b>  |                                    |
| Release of dangerous substances to the indoor environment                     |   | <b>No harmonized test method available</b>  |                                    |
| Acoustic adsorption index   | Sound adsorption  | <b>NPD</b>  |                                    |
| Direct airborne sound insulation index  | Sound adsorption  | <b>NPD</b>  |                                    |

**DECLARATION OF PERFORMANCE**

Table 1

| Thickness/(mm) | Thermal conductivity $\lambda_D$ /(W/mK) | Thermal resistance $R_D$ /(m <sup>2</sup> K/W) | Dimensional stability under specified temperature and humidity conditions |           |
|----------------|--|--|---|-----------|
|                |  |  | DS(70;90)   | DS(-20;0) |
| [T2]           |  |  |   |           |
| <b>20</b>      | <b>0.028</b>                             | <b>0.71</b>                                    | <b>3</b>  | <b>2</b>  |
| <b>30</b>      |  | <b>1.07</b>                                    |   |           |
| <b>40</b>      |  | <b>1.43</b>                                    |   |           |
| <b>50</b>      |  | <b>1.79</b>                                    |   |           |
| <b>60</b>      |  | <b>2.14</b>                                    |   |           |
| <b>70</b>      |  | <b>2.5</b>                                     |   |           |
| <b>80</b>      |  | <b>0.026</b>                                   |   |           |
| <b>90</b>      | <b>3.46</b>                              |  |   |           |
| <b>100</b>     | <b>3.85</b>                              |  |   |           |
| <b>120</b>     | <b>0.025</b>                             | <b>4.80</b>                                    |   |           |
| <b>140</b>     |  | <b>5.60</b>                                    |   |           |
| <b>160</b>     |  | <b>6.40</b>                                    |   |           |
| <b>180</b>     |  | <b>7.20</b>                                    |   |           |
| <b>200</b>     |  | <b>8.00</b>                                    |   |           |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:

Fabio Raggiotto, technical manager