

### STIFERITE Spa

Viale Navigazione Interna, 54 - 35129 Padova Tel +39 049 8997911 - Fax + 39 049 774727 http://www. stiferite.com - email info@stiferite.com



### **DECLARATION OF PERFORMANCE**

#### n.129 CPR 10/04/2023

Pag. 1/3

- 1. Unique identification code of the product type: STIFERITE BB
- 2. Batch number: See CE mark label and marking on boards
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacter: **Thermal insulation for building**
- 4. Name, registered trade or registered trade mark name and contact address of manufacture:

STIFERITE SpA

Viale Navigazione Interna, 54

35129 Padova (Italy)

- 5. Name and contact address of authorised representative whose mandate covers: -
- 6. System or systems of assessment and verification of constancy of performance of the construction product: AVCP 3
- 7. In case of declaration of performance concerning a construction product covered by a harmonised standard:

CSI S.p.A.

**IDENTIFICATION NUMBER: 0497** 

Performed the test reports on the declared characteristics under system AVCP 3

and

FORSCHUNGSINSTITUT FÜR WÄRMESCHUTZ E. V. MÜNCHEN FIW MÜNCHEN

**IDENTIFICATION NUMBER: 0751** 

Performed the test reports on the declared characteristics under system AVCP 3

and

L.S. FIRE TESTING INSTITUTE SRL

**IDENTIFICATION NUMBER: 2479** 

Performed the test reports on the declared characteristics under system AVCP 3

and

ISTITUTO GIORDANO S.P.A.

**IDENTIFICATION NUMBER: 0407** 

Performed the test reports on the declared characteristics under system AVCP 3

and

**TECNALIA R&I CERTIFICACION, S.L.** 

**IDENTIFICATION NUMBER: 1239** 

Performed the test reports on the declared characteristics under system AVCP 3

- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: –
- 9. Declaration performance:



# STIFERITE Spa

Viale Navigazione Înterna, 54 - 35129 Padova Tel +39 049 8997911 - Fax + 39 049 774727 http://www. stiferite.com - email info@stiferite.com



# DECLARATION OF PERFORMANCE

Pag. 2/3

Essential Characteristics	eristics Performance		Harmonised technical specification	
Thermal resistance	Thermal resistance R <sub>D</sub> /(m <sup>2</sup> K/W)	See table 1		
Thermal conductivity	Thermal conductivity λ <sub>D</sub> /(W/mK)			
Thickness	Thickness d <sub>N</sub> /(mm)	-		
Length and width	< 1000 mm	± 5 mm		
	1001 a 2000 mm	± 7.5 mm		
	2001 a 4000 mm	± 10 mm		
	> 4000 mm	15 mm		
Reaction to fire	Reaction to fire /(Euroclass)	F		
Continuous glowing combustion		No harmonized test method available		
Durability of reaction to fire against heat, weathering, ageing/degradation		Reaction to fire doesn't change		
Durability of thermal resistance against heat, weathering,	Durability of thermal resistance ageing/degradation	Thermal resistance doesn't change		
ageing/degradation	Dimensional stability under specified temperature and humidity conditions	See table 1		
	Deformation under specified compressive load and temperature conditions	<5 [DLT(1)5]	EN 13165: 2016	
Tensile strength	Tensile strength perpendicolar to the face /(kPa)	40 [TR40]		
Compressive strength	Compressive strength/(kPa)	150 [CS(10/Y)150]		
Durability of compressive strength against ageing/degradation	Compressive creep	<2 [CC(1.5/1.0/50)25]		
Water permeability	Water absorption - short term by partial immersion/(kg/m²)	0.3 [WS(P)0.2]		
	Water absorption - long term by total immersion /(%)	5 [WL(T)2]		
	Flatness after one sided wetting	≤ 10 mm [FW 10]		
Water vapor transmission	Water vapour transmission	MU 87 ± 19		
Release of dangerous substances to the indoor environment		No harmonized test method available		
Acoustic adsorption index	Sound adsorption	NPD		
Direct airbone sound insulation index	Sound adsorption	NPD		

_	aration of	Stiferite BB	Rev. 4 del 10/04/2023	Compiled by: F. Raggiotto	Verified by: L. Tolin	Approved by: P. Stimamiglio
---	------------	--------------	-----------------------	---------------------------	-----------------------	-----------------------------



## STIFERITE Spa

Viale Navigazione Înterna, 54 - 35129 Padova Tel +39 049 8997911 - Fax + 39 049 774727 http://www. stiferite.com - email info@stiferite.com



## **DECLARATION OF PERFORMANCE**

Pag. 3/3

#### Table 1

Spessore/(mm)	Conducibilità termica λ <sub>D</sub> /(W/mK)	Resistenza termica R <sub>D</sub> /(m <sup>2</sup> K/W)	Stabilità dimensionale sotto specifiche	
			condizioni di temperatura ed umidità	
[T2]	7		DS(70;90)	DS(-20;0)
20	0.007	0.74	2	
30	0.027	1.11	_	
40	_	1.48	3	
50		1.92		
60		2.31		2
70	0.026	2.59	4	
80		3.08	7	
90		3.46		
100	0.025	4.00		

**10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:

Padova, 10/04/2023

Fabio Raggiotto, technical manager

Her Eff