

STIFERITE Spa

Viale Navigazione Interna, 54 - 35129 Padova Tel +39 049 8997911 - Fax + 39 049 774727 http://www.stiferite.com - email info@stiferite.com



DECLARATION OF PERFORMANCE

n.62 CPR 27/03/2017

Pag. 1/3

- 1. Unique identification code of the product type: **STIFERITE GTE**
- 2. Batch number: See CE mark label and marking on boards
- **3.** Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacter: **Thermal insulation for building**
- 4. Name, registered trade or registered trade mark name and contact address of manufacture:

STIFERITE Spa

Viale Navigazione Interna, 54

35129 Padova (Italy)

- 5. Name and contact address of authorised representative whose mandate covers: -
- 6. System or systems of assessment and verification of constancy of performance of the construction product: AVCP 3
- 7. In case of declaration of performance concerning a construction product covered by a harmonised standard:

CSI S.p.A.

IDENTIFICATION NUMBER: 0497

Performed the test reports on the declared characteristics under system AVCP 3

And

ISTITUTO GIORDANO S.p.A.

IDENTIFICATION NUMBER: 0407

Performed the test reports on the declared characteristics under system AVCP 3

And

FIW Forschungsinstitut für Wärmeschutz e.V. München

IDENTIFICATION NUMBER: 0751

Performed the test reports on the declared characteristics under system AVCP 3

- **8.** In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: –
- 9. Declaration performance:

| Essential Characteristics | | | Harmonised technical specification |
|---------------------------|---|----------------------|------------------------------------|
| Thermal resistance | Thermal resistance R _D /(m ² K/W) | See table 1 | |
| Thermal conductivity | Thermal conductivity $\lambda_D/(W/mK)$ | | |
| Thickness | Thickness d _N /(mm) | | |
| Length and width | < 1000 mm | ± 5 mm | |
| | 1001 a 2000 mm | ± 7.5 mm | EN 13165:2016 |
| | 2001 a 4000 mm | ± 10 mm | |
| | > 4000 mm | 15 mm | |
| Reaction to fire | Reaction to fire /(Euroclass) | E | |
| | Reaction to fire – end use/(Euroclass) | B s1 d0 (steel deck) | |

| Declaration of performance Stiferite GTE Rev. 3 del 10/04/2018 Compiled by: F. Raggio | iotto Verified by: L. Tolin | Approved by: P. Stimamiglio | |
|---|-----------------------------|-----------------------------|--|
|---|-----------------------------|-----------------------------|--|



STIFERITE Spa

Viale Navigazione Înterna, 54 - 35129 Padova Tel +39 049 8997911 - Fax + 39 049 774727 http://www.stiferite.com - email info@stiferite.com



DECLARATION OF PERFORMANCE

| Essential Characteristics | Performance | | Harmonised technical specification |
|---|---|-------------------------------------|------------------------------------|
| Continuous glowing combustion | | No harmonized test method available | |
| Durability of reaction to fire against heat, weathering, ageing/degradation | | Reaction to fire doesn't change | |
| Durability of thermal resistance against heat, weathering, | Durability of thermal resistance ageing/degradation | Thermal resistance doesn't change | |
| ageing/degradation | Dimensional stability under specified temperature and humidity conditions | See table 1 | |
| | Deformation under specified compressive load and temperature conditions | NPD | |
| Tensile strength | Tensile strength perpendicolar to the face /(kPa) | 30 [TR30] | |
| Compressive strength | Compressive strength/(kPa) | 150 [CS(10/Y)150] | |
| Durability of compressive strength against ageing/degradation | Compressive creep | [CC(3/2.5/30)130] | EN 13165:2016 |
| Water permeability | Water absorption - short term by partial immersion/(kg/m²) | 0.1 [WS(P)0.2] | |
| | Water absorption - long term by total immersion /(%) | 1 [WL(T)2] | |
| | Flatness after one sided wetting | ≤ 10 mm [FW 10] | |
| Water vapor transmission | Water vapour transmission | MU >89900 | |
| Release of dangerous substances to the indoor environment | | No harmonized test method available | |
| Acoustic adsorption index | Sound adsorption | NPD | |
| Direct airbone sound insulation index | Sound adsorption | NPD | |

| Declaration of | Stiferite GTE | Rev. 3 del 10/04/2018 | Compiled by: F. Raggiotto | Verified by: L. Tolin | Approved by: |
|----------------|---------------|-----------------------|---------------------------|-----------------------|----------------|
| performance | | | | | P. Stimamiglio |

Pag. 3/3



STIFERITE Spa

Viale Navigazione Înterna, 54 - 35129 Padova Tel +39 049 8997911 - Fax + 39 049 774727 http://www.stiferite.com - email info@stiferite.com



DECLARATION OF PERFORMANCE

Table 1

| Thickness/(mm) | Thermal conductivity λ _D /(W/mK) | Thermal resistance R _D /(m ² K/W) | Dimensional stabil temperature and h | |
|----------------|---|---|---|-----------|
| [T2] | 7 | | DS(70;90) | DS(-20;0) |
| 20 | | 0.91 | 3 | |
| 30 | - | 1.36 | | |
| 40 | | 1.82 | | |
| 50 | | 2.27 | | |
| 60 | | 2.73 | | |
| 70 | 0.022 | 3.18 | 4 | 2 |
| 80 | | 3.64 | . 4 | |
| 90 | 1 | 4.09 | | |
| 100 | | 4.55 | | |
| 120 | | 5.45 | | |
| 140 | | 6.36 | | |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:

Padova, 10/04/2018

Fabio Raggiotto, technical manager