

DECLARATION OF PERFORMANCE

n.15 CPR 01/07/2013

Pag. 1/3

1. Unique identification code of the product – type: **STIFERITE GT**
2. Batch number: **See CE mark label and marking on boards**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Thermal insulation for building**
4. Name, registered trade or registered trade mark name and contact address of manufacture:

STIFERITE srl
Viale Navigazione Interna, 54
35129 Padova (Italy)

5. Name and contact address of authorised representative whose mandate covers: –
6. System or systems of assessment and verification of constancy of performance of the construction product: **AVCP 3**
7. In case of declaration of performance concerning a construction product covered by a harmonised standard:

CSI S.p.A.
IDENTIFICATION NUMBER: 0497
Performed the test reports on the declared characteristics under system AVCP 3
And
ISTITUTO GIORDANO S.p.A.
IDENTIFICATION NUMBER: 0407
Performed the test reports on the declared characteristics under system AVCP 3

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: –
9. Declaration performance:

Essential Characteristics	Performance		Harmonised technical specification
Thermal resistance	Thermal resistance $R_D/(m^2K/W)$	See table 1	EN 13165: 2012
Thermal conductivity	Thermal conductivity $\lambda_D/(W/mK)$		
Thickness	Thickness $d_W/(mm)$		
Length and width	< 1000 mm	± 5 mm	
	1001 a 2000 mm	± 7.5 mm	
	2001 a 4000 mm	± 10 mm	
	> 4000 mm	15 mm	
Reaction to fire	Reaction to fire /(Euroclass)	F	
Continuous glowing combustion		No harmonized test method available	
Durability of reaction to fire against heat, weathering, ageing/degradation		Reaction to fire doesn't change	

Declaration of performance	Stiferite GT	Rev. 1 del 01/04/2016	Compiled by: F. Raggiotto	Verified by: L. Tolin	Approved by: P. Stimamiglio
----------------------------	--------------	-----------------------	---------------------------	-----------------------	-----------------------------

DECLARATION OF PERFORMANCE

Essential Characteristics	Performance		Harmonised technical specification
Durability of thermal resistance against heat, weathering, ageing/degradation	Durability of thermal resistance ageing/degradation	Thermal resistance doesn't change	EN 13165: 2012
	Dimensional stability under specified temperature and humidity conditions	See table 1	
	Deformation under specified compressive load and temperature conditions	NPD	
Tensile strength	Tensile strength perpendicular to the face /(kPa)	NPD	
Compressive strength	Compressive strength/(kPa)	150 [CS(10/Y)150]	
Durability of compressive strength against ageing/degradation	Compressive creep	NPD	
Water permeability	Water absorption - short term by partial immersion/(kg/m ²)	0.1 [WS(P)0.2]	
	Water absorption - long term by total immersion /(%)	1 [WL(T)2]	
	Flatness after one sided wetting	≤ 10 mm [FW 10]	
Water vapor transmission	Water vapour transmission	MU 148 ± 24	
Release of dangerous substances to the indoor environment		No harmonized test method available	
Acoustic adsorption index	Sound adsorption	NPD	
Direct airborne sound insulation index	Sound adsorption	NPD	

DECLARATION OF PERFORMANCE

Table 1

Thickness/(mm)	Thermal conductivity λ_D /(W/mK)	Thermal resistance R_D /(m ² K/W)	Dimensional stability under specified temperature and humidity conditions	
			DS(70;90)	DS(-20;0)
[T2]				
20	0.023	0.87	3	2
30		1.30	4	
40		1.74		
50		2.17		
60		2.61		
70		3.04		
80		3.48		
90		3.91		
100		4.35		
120		5.22		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:

Fabio Raggiotto, technical manager